



FOTON

AUMARK



Mobimotors

Aumark



FOTON

Mobimotors

Vehicle Model

BJ1128

Engine

Model	Cummins ISF3.8s 3168
Displacement (L)	3,76
Type	4 cylinder, Common Rail Turbocharged with Intercooler
Max power (Hp/rpm)	170 HP
Max torque (NM/rpm)	550 NM

Gearbox

Model	ZF6S558
Type	Cabel Shift Manual
No. of Gears	6F 1R

Complete vehicle dimension parameters

Wheelbase (mm)	4700
Cab width (mm)	2060
Overall Dimensions (L×W×H)	8220×2310×2470

Brake

System	Full Air Dual Circuit, with air dryer and auto brake lining adjustment
ABS	Standard
Type	Front - Disc Rear - Drum
Auxiliary brake	Exhaust Brake

Tire

Model	9R22.5-14 Ply Tubeless
Quantity	6+1

Suspension

Front suspension/leaf spring number	Multi Leaf spring - 9 Numbers
Rear suspension/leaf spring number	Multi Leaf spring with Helper - 8+6 Numbers

Axle

Front Axle Capacity (Kg)	3600
Rear Axle Capacity (Kg)	8000
Rear Axle Ratio	5,286

Weight

GVW (Kg)	12140
----------	-------

Axle

Type	Day Cab
Air conditioning	Standard

Fuel tank

Capacity and material	200L plastic
-----------------------	--------------

Battery

Battery voltage	24V
-----------------	-----

Features

- 1.Cruise Control for Better Driver Comfort;
- 2.Manual control & Windows/Door;
- 3.MP3+Bluetooth.