



FOTON

AUMAN C TIPPER

6×4-20M³



Mobimotors

AUMAN Tipper 6×4-20m³



FOTON

Mobimotors

Base informations

Drive Style	6*4
Steering wheel position	Right
Platform	C
Vehicle model	BJ3259DLPKE-RA

Chassis dimension parameters

Wheelbase (mm)	4100+1350
----------------	-----------

Complete vehicle mass parameter

Chassis kerb weight (kg)	10125
GCW (kg)	55000

Complete vehicle performance parameter

Maximum speed (km/h)	Full load 95
Maximum climbing capacity, % (full load)	34

Cab

Body type	EST-2490-Flat Roof With Electric A/C
Carrying number	2

Engine

Engine Model	ISGe3-350
Displacement (L)	10,5
Max power (ps/rpm)	350/1900
Max torque (Nm/rpm)	1800/1000
Engine Brand	Cummins
Emission	Euro III

Clutch

Clutch Type	φ430 pull type diaphragm spring clutch
Plate diameter	Φ430

Gearbox

Gearbox Model	HW19712
Gearbox Brand	DACHI 12MT

Suspension

Front suspension/leaf spring number	9
Rear suspension/leaf spring number	12

Front axle

Front axle Rated load	9T
Front axle Brake type	Drum brakes

Rear axle

Rear axle Model	16T/BENZ
Rated load/gear ratio	16T/5.26
Rear axle Brake type	Drum brakes

Tyre

Tyre Model	12.00R20 20PR
Tyre Quantity	10+1

Frame

External width (mm)	F865mm/R865mm
Stringer cross section (mm)	225/320×90×(8+7)

Steering Gear

Steering Gear Model	AM105L-SR
---------------------	-----------

Fuel tank

Fuel tank Cubage and material	350L (Aluminium alloy)
-------------------------------	------------------------

Others Specs

Cabin Suspension	Spiral spring
Cabin lifting style	Electric lifting
Windows+Door	Electric Window+Center control
Seats	Air Seat
Media	MP3+Radio

Body Type

Body Dimension(mm)	5.6m*2.3m*1.5m, U shape (20 m³)
Floor/Side Thickness (mm)	Floor 8mm,Side 6mm
Material	Q345 high-strength steel
Lifting Type	Front lift